




**Newlay  
Asphalt**

2024		 <b>UK CA</b> 0086		<b>BS EN 13108-4:2016</b>	<u>UKCA Mark ref. NAAC007 Dated 01 Jan 2024</u>
<b>Bituminous mixtures - Material specifications Part 4: Hot Rolled Asphalt</b>					
<b>Newlay Asphalt Limited</b>					
<b>Elite House, Spellowgate, Driffield, East Yorkshire, YO25 5UP</b>					
<b>Source and material description: Newlay Asphalt Dewsbury Plant - Part 4: Hot Rolled Asphalt - HRA 30/10 Surface 100/150</b>					
Intended use: For use on roads, airfields and other trafficked areas					
Attestation Level 2+ Certified by UK Approved Body BSI - Ref. 0086 - CPR - 623633					
<b>Essential Characteristics</b>		<b>Declared values</b>			
		<b>Sieve Size (mm)</b>	<b>Passing (%)</b>	<b>Tolerance</b>	
Target Composition (Grading)		14.000	100.00	As EN 13108-1	
		10.000	96.00	As EN 13108-1	
		6.300	73.00	As EN 13108-1	
		2.000	65.00	As EN 13108-1	
		0.500	61.00	As EN 13108-1	
		0.250	30.00		
		0.063	7.00	As EN 13108-1	
Binder Content		7.70%			
Temperature Range		120 to 170 Degees C.			
Void Content (Maximum)		V <sub>max</sub> NR			
Void Content (Minimum)		V <sub>min</sub> NR			
Water Sensitivity		ITSR NR			
Resistance to Abrasion		ABR NR			
Reaction to Fire		Euroclass CfI NR			
Stiffness (Maximum)		S <sub>max</sub> NR			
Stiffness (Minimum)		S <sub>min</sub> NR			
Resistance to Permanent Deformation		F <sub>cmax</sub> NR			
Coarse Aggregate		BS EN 13043 - As Approved Supplier List			
Fine Aggregate		BS EN 13043 - As Approved Supplier List			
Filler Aggregate		BS EN 13043 (Natural or Extracted) - As Approved Supplier List			
Declaration of Performance		In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site <a href="https://www.newlayasphalt.co.uk/certification">https://www.newlayasphalt.co.uk/certification</a> (or will be supplied directly). The appropriate DoP is referenced NAAC002 UKCA DOP on the UKCA Regulations page and/or on formal documentation.			CPR DoP Electronic Provision No. 305/2011