




**Newlay
Asphalt**

2024	 UK CA 0086	BS EN 13108-1:2016	<u>UKCA Mark ref. NAAC011 Dated 01 Jan 2024</u>
Bituminous mixtures - Material specifications Part 1: Asphalt Concrete			
Newlay Asphalt Limited			
Elite House, Spellowgate, Driffield, East Yorkshire, YO25 5UP			
Source and material description: Newlay Asphalt Dewsbury Plant - Asphalt Concrete - AC14 Close Surface 100/150			
Intended use: For use on roads, airfields and other trafficked areas			
Attestation Level 2+ Certified by UK Approved Body BSI - Ref. 0086 - CPR - 623633			
Essential Characteristics	Declared values		
Target Composition (Grading)	Sieve Size (mm)	Passing (%)	Tolerance
	20.000	100.00	As EN 13108-1
	14.000	96.00	As EN 13108-1
	10.000	75.00	As EN 13108-1
	6.300	50.00	As EN 13108-1
	2.000	24.00	As EN 13108-1
	1.000	18.00	As EN 13108-1
	0.063	4.50	As EN 13108-1
Binder Content	4.60%		
Temperature Range	120 to 170 Degees C.		
Void Content (Maximum)	V _{max} NR		
Void Content (Minimum)	V _{min} NR		
Water Sensitivity	ITSR NR		
Resistance to Abrasion	ABR NR		
Reaction to Fire	Euroclass Cfl NR		
Stiffness (Maximum)	S _{max} NR		
Stiffness (Minimum)	S _{min} NR		
Resistance to Permanent Deformation	F _{cmax} NR		
Coarse Aggregate	BS EN 13043 - As Approved Supplier List		
Fine Aggregate	BS EN 13043 - As Approved Supplier List		
Filler Aggregate	BS EN 13043 (Natural or Extracted) - As Approved Supplier List		
Declaration of Performance	<small>In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site https://www.newlayasphalt.co.uk/certification (or will be supplied directly). The appropriate DoP is referenced NAAC002 UKCA DOP on the UKCA Regulations page and/or on formal documentation.</small>		CPR DoP Electronic Provision No. 305/2011