

2024		C EN 42400 4-0040		
UK		S EN 13108-1:2016		NAAC002 Dated 01 Jan 2024
ČÀ		Bituminous mixtures - Material specifications Part 1: Asphalt Concrete		
		Newlay Asphalt Limited		
0086		Elite House, Spellowgate, Driffield, East Yorkshire, YO25 5UP		
Source and material description: Newlay Asphalt Dewsbury Plant - Asphalt Concrete - AC6 Dense Surface 100/150				
Intended use: For use on roads, airfields and other trafficked areas				
Attestation Level 2+ Certified by UK Approved Body BSI - Ref. 0086 - CPR - 623633				
Essential Characteristics	Declared values			
	Sieve Size (mm)	Passing (%)	Tolerance	
Target Composition (Grading)	10.000 6.300 2.000 1.000 0.250 0.063 Note - RAP may be included at an addition rate of up to	100.00 96.00 44.00 29.00 16.00 5.70 20%. The final grading above will be unchanged.	As EN 13108-1 As EN 13108-1 As EN 13108-1 As EN 13108-1 As EN 13108-1 As EN 13108-1	
Binder Content	6.00%			
Temperature Range	120 to 170 Degees C. (Note - 'Warm Mix' parameters are 30 Deg. C less than those stated herein)			
Void Content (Maximum)	V _{max NR}			
Void Content (Minimum)	Vmin NR			
Water Sensitivity	ITSR NR			
Resistance to Abrasion	ABR NR			
Reaction to Fire	Euroclass Cfl NR			
Stiffness (Maximum)	Smax NR			
Stiffness (Minimum)	Smin NR			
Resistance to Permanent Deformation	Fcmax NR			
Coarse Aggregate	BS EN 13043 - As Approved Supplier List			
Fine Aggregate	BS EN 13043 - As Approved Supplier List			
Filler Aggregate	BS EN 13043 (Natural or Extracted) - As Approved Supplier List			
Declaration of Performance	In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site https://www.newlayasphalt.co.uk/certification (or will be supplied directly). The appropriate DoP is referenced NAAC002 UKCA DOP on the UKCA Regulations page and/or on formal documentation.			