

UK

0086

2024

BS EN 13108-4	:2016
---------------	-------

UKCA Mark ref. NAAC007 Dated 01 Jan 2024

Bituminous mixtures - Material specifications Part 4: Hot Rolled Asphalt

Newlay Asphalt Limited

Elite House, Spellowgate, Driffield, East Yorkshire, YO25 5UP

Source and material description: Newlay Asphalt Dewsbury Plant - Part 4: Hot Rolled Asphalt - HRA 30/10 Surface 100/150

Intended use: For use on roads, airfields and other trafficked areas

Attestation Level 2+ Certified by UK Approved Body BSI - Ref. 0086 - CPR - 623633

Essential Characteristics	Declared values				
	Sieve Size (mm)	Passing (%)	Tolerance		
	14.000	100.00	As EN 13108-4		
Target Composition (Creding)	10.000	96.00	As EN 13108-4		
Target Composition (Grading)	6.300	73.00	As EN 13108-4		
	2.000	65.00	As EN 13108-4		
	0.500	61.00	As EN 13108-4		
	0.250	30.00	As EN 13108-4		
	0.063 Note - RAP may be included at an addition rate of up to 20%. The	7.00 final grading above will be unchanged.	As EN 13108-4		
Binder Content	7.70%				
Temperature Range	120 to 170 Degees C. (Note - 'Warm Mix' parameters are 30 Deg. C less than those stated herein)				
Void Content (Maximum)	Vmax NR				
Void Content (Minimum)	Vmin NR				
Water Sensitivity	ITSR NR				
Resistance to Abrasion	ABR NR				
			IX		
Reaction to Fire	Euroclass Cfl NR				
Stiffness (Maximum)	Smax NR				
Stiffness (Minimum)	Smin NR				
Resistance to Permanent Deformation	Fcmax NR				
Coarse Aggregate	BS EN 13043 - As Approved Supplier List				
Fine Aggregate	BS EN 13043 - As Approved Supplier List				
Filler Aggregate	BS EN 13043 (Natural or Extracted) - As Approved Supplier List				
Declaration of Performance	https://www.newlayasphalt.co.uk/certification (or will b	the Declaration of Performance (DoP) is he e supplied directly). The appropriate DoP ations page and/or on formal documentati	is referenced NAAC002 UKCA	CPR DoP Electronic Provision No 305/2011	