

2024



BS EN 13108-1:2016

UKCA Mark ref. NAAC001 Dated 01 Jan 2024

Bituminous mixtures - Material specifications Part 1: Asphalt Concrete

Newlay Asphalt Limited

Elite House, Spellowgate, Driffield, East Yorkshire, YO25 5UP

Source and material description: Newlay Asphalt Dewsbury Plant - Asphalt Concrete - AC10 Close Surface 100/150 & 40/60

Intended use: For use on roads, airfields and other trafficked areas

Attestation Level 2+ Certified by UK Approved Body BSI - Ref. 0086 - CPR - 623633

Essential Characteristics	Declared values			
	Sieve Size (mm)	Passing (%)	Tolerance	
Target Composition (Grading)	14.000 10.000 6.300 2.000 1.000 0.063 Note - RAP may be included at an addition rate of up to 20%. The	100.00 98.00 68.00 29.00 21.00 5.00 final grading above will be unchanged.	As EN 13108-1 As EN 13108-1 As EN 13108-1 As EN 13108-1 As EN 13108-1 As EN 13108-1	
Binder Content	5.20%			
Temperature Range	125 PEN (blend) - 120 to 170 Degees C. (Note - 'Warm Mix' parameters are 20 Deg. C less than those stated herein). 50 PEN (40/60) - 120 to 190 Degees C. (Note - 'Warm Mix' parameters are 20 Deg. C less than those stated herein)			
Void Content (Maximum)	V _{max NR}			
Void Content (Minimum)	V _{min NR}			
Water Sensitivity	ITSR NR			
Resistance to Abrasion	ABR NR			
Reaction to Fire	Euroclass Cfl _{NR}			
Stiffness (Maximum)	Smax NR			
Stiffness (Minimum)	Smin NR			
Resistance to Permanent Deformation	Fcmax NR			
Coarse Aggregate	BS EN 13043 - As Approved Supplier List			
Fine Aggregate	BS EN 13043 - As Approved Supplier List			
Filler Aggregate	BS EN 13043 (Natural or Extracted) - As Approved Supplier List			
Declaration of Performance	In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site https://www.newlayasphalt.co.uk/certification (or will be supplied directly). The appropriate DoP is referenced NAAC002 UKCA DOP on the UKCA Regulations page and/or on formal documentation. CPR DoP Electronic Provision No. 305/2011			