

²⁰²⁴	BS EN 13108-1:2016 UKCA Mark ref. NAAC002 Dated 01 Jan 2024
	Bituminous mixtures - Material specifications Part 1: Asphalt Concrete
	Newlay Asphalt Limited
0086	Elite House, Spellowgate, Driffield, East Yorkshire, YO25 5UP
Source and material description: Newlay Asphalt Dewsbury Plant - Asphalt Concrete - AC6 Dense Surface 100/150 & 160/220	
Intended use: For use on roads, airfields and other trafficked areas	
Attestation Level 2+ Certified by UK Approved Body BSI - Ref. 0086 - CPR - 623633	
Essential Characteristics	Declared values
	Sieve Size (mm) Passing (%) Tolerance
Target Composition (Grading)	10.000 100.00 As EN 13108-1 6.300 96.00 As EN 13108-1 2.000 44.00 As EN 13108-1 1.000 29.00 As EN 13108-1 0.250 16.00 As EN 13108-1 0.063 5.70 As EN 13108-1 Note - RAP may be included at an addition rate of up to 20%. The final grading above will be unchanged. Here and the second sec
Binder Content	6.00%
Temperature Range	125 PEN (blend) - 120 to 170 Degees C. (Note - 'Warm Mix' parameters are 20 Deg. C less than those stated herein). 190 PEN (160/220) - 120 to 165 Degees C. (Note - 'Warm Mix' parameters are 20 Deg. C less than those stated herein) 190
Void Content (Maximum)	V _{max NR}
Void Content (Minimum)	V _{min NR}
Water Sensitivity	ITSR NR
Resistance to Abrasion	ABR NR
Reaction to Fire	Euroclass Cfl NR
Stiffness (Maximum)	Smax NR
Stiffness (Minimum)	Smin NR
Resistance to Permanent Deformation	Fcmax NR
Coarse Aggregate	BS EN 13043 - As Approved Supplier List
Fine Aggregate	BS EN 13043 - As Approved Supplier List
Filler Aggregate	BS EN 13043 (Natural or Extracted) - As Approved Supplier List
Declaration of Performance	In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site https://www.newlayasphalt.co.uk/certification (or will be supplied directly). The appropriate DoP is referenced NAAC002 UKCA DOP on the UKCA Regulations page and/or on formal documentation.