

UK

0086

2024

BS	EN	13108-5:2016
----	----	--------------

UKCA Mark ref. NAAC008 Dated 01 Jan 2024

Bituminous mixtures - Material specifications Part 5: Stone Mastic Asphalt

Newlay Asphalt Limited

Elite House, Spellowgate, Driffield, East Yorkshire, YO25 5UP

Source and material description: Newlay Asphalt Dewsbury Plant - Part 5: Stone Mastic Asphalt - 14mm SMA 100/150

Intended use: For use on roads, airfields and other trafficked areas

Attestation Level 2+ Certified by UK Approved Body BSI - Ref. 0086 - CPR - 623633

Essential Characteristics	Declared values					
	Sieve Size (mm)	Passing (%)	Tolerance			
	20.000	100.00	As EN 13108-5			
	14.000	95.00	As EN 13108-5			
Target Composition (Grading)	10.000	57.00	As EN 13108-5			
		33.00	As EN 13108-5 As EN 13108-5			
	6.300					
	2.000	23.00	As EN 13108-5			
	0.063	9.00	As EN 13108-5			
	Note - RAP may be included at an addition rate of up to 20%. The fir	al grading above will be unchanged.				
Binder Content	5.80%					
Fibre Content	0.30%					
Temperature Range	120 to 170 Degees C. (Note - 'Warm Mix' parameters are 20 Deg. C less than those stated herein)					
Void Content (Maximum)	Vmax NR					
Void Content (Minimum)	Vmin NR					
Water Sensitivity	ITSR NR					
Resistance to Abrasion	ABR NR					
Reaction to Fire	Euroclass Cfl NR					
Stiffness (Maximum)	Smax NR					
· · · · · ·						
Stiffness (Minimum)	Smin NR					
Resistance to Permanent Deformation	Fcmax NR					
Coarse Aggregate	BS EN 13043 - As Approved Supplier List					
Fine Aggregate	BS EN 13043 - As Approved Supplier List					
Filler Aggregate	BS EN 13043 (Natural or Extracted) - As Approved Supplier List					
Declaration of Performance	https://www.newlayasphalt.co.uk/certification (or will b	with the CPR regulations, the Declaration of Performance (DoP) is held on our web site co.uk/certification (or will be supplied directly). The appropriate DoP is referenced NAAC002 UKCA DOP on the UKCA Regulations page and/or on formal documentation. CPR DoP Electronic Provision No. 305/2011				