



CPR Declaration of Performance (DoP)

DoP reference:

NAAC009 UKCA DOP

1. Unique identification code of the product type (in combination with point 2):

BS EN 13108-4:2016 Bituminous mixtures - Material specifications Part 4: Hot Rolled Asphalt

2. Identification of the construction product:

Newlay Asphalt Dewsbury Plant - Part 4: Hot Rolled Asphalt - HRA 30/14 Surface 100/150

3. Intended use:

BS EN 13108-4:2016 Bituminous mixtures
For use on roads, airfields and other trafficked areas

4. Company name:

Newlay Asphalt Limited
Elite House
Spellowgate
Driffield
East Yorkshire
YO25 5UP

5. Authorised representative:

Jamie Brown (address as above)

6. System of assessment:

Attestation Level 2+

7. Standard and UK Approved body:

Attestation Level 2+ Certified by UK Approved Body BSI - Ref. 0086 - CPR – 623633; a UKAS accredited certification body and a UK approved body under Article 9 of the Construction Products Regulation (EU) No 305/2011 as amended by The Construction Products (Amendment etc.) (EU Exit) Regulations 2019 (S.I. 2019/465).

8. European Technical Assessment (ETA):

Not applicable

continued...

9. Declared performance:

Essential Characteristics	Declared values		
Target Composition (Grading)	Sieve Size (mm)	Passing (%)	Tolerance
	20.000	100.00	As EN 13108-4
	14.000	96.00	As EN 13108-4
	10.000	77.00	As EN 13108-4
	2.000	66.00	As EN 13108-4
	0.500	62.00	As EN 13108-4
	0.250	30.00	As EN 13108-4
	0.063	7.00	As EN 13108-4
<small>Note - RAP may be included at an addition rate of up to 20%. The final grading above will be unchanged.</small>			
Binder Content	7.70%		
Temperature Range	120 to 170 Degees C. (Note - 'Warm Mix' parameters are 20 Deg. C less than those stated herein)		
Void Content (Maximum)	V _{max} NR		
Void Content (Minimum)	V _{min} NR		
Water Sensitivity	ITSR NR		
Resistance to Abrasion	ABR NR		
Reaction to Fire	Euroclass CfI NR		
Stiffness (Maximum)	S _{max} NR		
Stiffness (Minimum)	S _{min} NR		
Resistance to Permanent Deformation	F _{cmax} NR		
Coarse Aggregate	BS EN 12043 - As Approved Supplier List		
Fine Aggregate	BS EN 12043 - As Approved Supplier List		
Filler Aggregate	BS EN 12043 (Natural or Extracted) - As Approved Supplier List		
Declaration of Performance	In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site https://www.newlayasphalt.co.uk/certification (or will be supplied directly). The appropriate DoP is referenced NAAC002 UKCA DOP on the UKCA Regulations page and/or on formal documentation.		CPR DoP Electronic Provision No. 305/2011


10. Declaration

The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for any on behalf of the manufacturer by Jamie Brown (Director), issued at the address given in point 4, 01 Jan 2024.

Signature: *Jamie Brown*

Supporting information:

The UKCA Mark below was issued with your delivery ticket, or accompanying documentation in accordance with the CPR regulations. Accompanying documentation may include the quotation, order acknowledgement, invoice or direct email at the client's request (i.e. delivered either in hard-copy or electronic format within an email).

2024  0086	BS EN 13108-4:2016 UKCA Mark ref. NAAC009 Dated 01 Jan 2024 Bituminous mixtures - Material specifications Part 4: Hot Rolled Asphalt Newlay Asphalt Limited Elite House, Spellowgate, Driffield, East Yorkshire, YO25 5UP																								
Source and material description: Newlay Asphalt Dewsbury Plant - Part 4: Hot Rolled Asphalt - HRA 30/14 Surface 100/150																									
Intended use: For use on roads, airfields and other trafficked areas																									
Attestation Level 2+ Certified by UK Approved Body BSI - Ref. 0086 - CPR - 623633																									
Essential Characteristics	Declared values																								
Target Composition (Grading)	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Sieve Size (mm)</th> <th style="text-align: center;">Passing (%)</th> <th style="text-align: center;">Tolerance</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">20.000</td> <td style="text-align: center;">100.00</td> <td style="text-align: center;">As EN 13108-4</td> </tr> <tr> <td style="text-align: center;">14.000</td> <td style="text-align: center;">96.00</td> <td style="text-align: center;">As EN 13108-4</td> </tr> <tr> <td style="text-align: center;">10.000</td> <td style="text-align: center;">77.00</td> <td style="text-align: center;">As EN 13108-4</td> </tr> <tr> <td style="text-align: center;">2.000</td> <td style="text-align: center;">66.00</td> <td style="text-align: center;">As EN 13108-4</td> </tr> <tr> <td style="text-align: center;">0.500</td> <td style="text-align: center;">62.00</td> <td style="text-align: center;">As EN 13108-4</td> </tr> <tr> <td style="text-align: center;">0.250</td> <td style="text-align: center;">30.00</td> <td style="text-align: center;">As EN 13108-4</td> </tr> <tr> <td style="text-align: center;">0.063</td> <td style="text-align: center;">7.00</td> <td style="text-align: center;">As EN 13108-4</td> </tr> </tbody> </table>	Sieve Size (mm)	Passing (%)	Tolerance	20.000	100.00	As EN 13108-4	14.000	96.00	As EN 13108-4	10.000	77.00	As EN 13108-4	2.000	66.00	As EN 13108-4	0.500	62.00	As EN 13108-4	0.250	30.00	As EN 13108-4	0.063	7.00	As EN 13108-4
	Sieve Size (mm)	Passing (%)	Tolerance																						
	20.000	100.00	As EN 13108-4																						
	14.000	96.00	As EN 13108-4																						
	10.000	77.00	As EN 13108-4																						
	2.000	66.00	As EN 13108-4																						
	0.500	62.00	As EN 13108-4																						
	0.250	30.00	As EN 13108-4																						
0.063	7.00	As EN 13108-4																							
Note - RAP may be included at an addition rate of up to 20%. The final grading above will be unchanged.																									
Binder Content	7.70%																								
Temperature Range	120 to 170 Degees C. (Note - 'Warm Mix' parameters are 20 Deg. C less than those stated herein)																								
Void Content (Maximum)	V _{max} NR																								
Void Content (Minimum)	V _{min} NR																								
Water Sensitivity	ITSR NR																								
Resistance to Abrasion	ABR NR																								
Reaction to Fire	Euroclass CfI NR																								
Stiffness (Maximum)	S _{max} NR																								
Stiffness (Minimum)	S _{min} NR																								
Resistance to Permanent Deformation	F _{cmax} NR																								
Coarse Aggregate	BS EN 13043 - As Approved Supplier List																								
Fine Aggregate	BS EN 13043 - As Approved Supplier List																								
Filler Aggregate	BS EN 13043 (Natural or Extracted) - As Approved Supplier List																								
Declaration of Performance	<small>In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site https://www.newlayasphalt.co.uk/certification (or will be supplied directly). The appropriate DoP is referenced NAAC002 UKCA DOP on the UKCA Regulations page and/or on formal documentation.</small>	CPR DoP Electronic Provision No. 305/2011																							

Please contact us should you require any further information.