

2024



BS EN 13108-4:2016

UKCA Mark ref. NAAC009 Dated 01 Jan 2024

Bituminous mixtures - Material specifications Part 4: Hot Rolled Asphalt

Newlay Asphalt Limited

Elite House, Spellowgate, Driffield, East Yorkshire, YO25 5UP

Source and material description: Newlay Asphalt Dewsbury Plant - Part 4: Hot Rolled Asphalt - HRA 30/14 Surface 100/150

Intended use: For use on roads, airfields and other trafficked areas

Attestation Level 2+ Certified by UK Approved Body BSI - Ref. 0086 - CPR - 623633				
Essential Characteristics	Declared values			
	Sieve Size (mm)	Passing (%)	Tolerance	
Target Composition (Grading)	20.000 14.000 10.000 2.000 0.500 0.250 0.063 Note - RAP may be included at an addition rate of up to 20%. The	100.00 96.00 77.00 66.00 62.00 30.00 7.00 final grading above will be unchanged.	As EN 13108-4 As EN 13108-4 As EN 13108-4 As EN 13108-4 As EN 13108-4 As EN 13108-4	
Binder Content	7.70%			
Temperature Range	120 to 170 Degees C. (Note - 'Warm Mix' parameters are 20 Deg. C less than those stated herein)			
Void Content (Maximum)	V _{max} NR			
Void Content (Minimum)	V _{min} NR			
Water Sensitivity	ITSR NR			
Resistance to Abrasion		ABR NI	R	
Reaction to Fire	Euroclass Cfl NR			
Stiffness (Maximum)	Smax NR			
Stiffness (Minimum)	Smin NR			
Resistance to Permanent Deformation	Fcmax NR			
Coarse Aggregate	BS EN 13043 - As Approved Supplier List			
Fine Aggregate	BS EN 13043 - As Approved Supplier List			
Filler Aggregate	BS EN 13043 (Natural or Extracted) - As Approved Supplier List			
Declaration of Performance	https://www.newlayasphalt.co.uk/certification (or will be	the Declaration of Performance (DoP) is he e supplied directly). The appropriate DoP i ations page and/or on formal documentation	is referenced NAAC002 UKCA	CPR DoP Electronic Provision No. 305/2011