




**Newlay  
Asphalt**

2024		 <b>UK CA</b> 0086		<b>BS EN 13108-1:2016</b>	<u>UKCA Mark ref. NAAC010 Dated 01 Jan 2024</u>	
<b>Bituminous mixtures - Material specifications Part 1: Asphalt Concrete</b>						
<b>Newlay Asphalt Limited</b>						
<b>Elite House, Spellowgate, Driffield, East Yorkshire, YO25 5UP</b>						
<b>Source and material description: Newlay Asphalt Dewsbury Plant - Asphalt Concrete - AC20 Open Graded Binder 100/150 &amp; 40/60</b>						
Intended use: For use on roads, airfields and other trafficked areas						
Attestation Level 2+ Certified by UK Approved Body BSI - Ref. 0086 - CPR - 623633						
<b>Essential Characteristics</b>		<b>Declared values</b>				
		<b>Sieve Size (mm)</b>	<b>Passing (%)</b>	<b>Tolerance</b>		
Target Composition (Grading)		31.500	100.00	As EN 13108-1		
		20.000	97.00	As EN 13108-1		
		14.000	54.00	As EN 13108-1		
		6.300	25.00	As EN 13108-1		
		2.000	17.00	As EN 13108-1		
		0.063	4.10	As EN 13108-1		
<small>Note - RAP may be included at an addition rate of up to 20%. The final grading above will be unchanged.</small>						
Binder Content		3.80%				
Temperature Range		125 PEN (blend) - 120 to 170 Degees C. (Note - 'Warm Mix' parameters are 20 Deg. C less than those stated herein). PEN (40/60) - 120 to 190 Degees C. (Note - 'Warm Mix' parameters are 20 Deg. C less than those stated herein)			50	
Void Content (Maximum)		V <sub>max</sub> NR				
Void Content (Minimum)		V <sub>min</sub> NR				
Water Sensitivity		ITSR NR				
Resistance to Abrasion		ABR NR				
Reaction to Fire		Euroclass Cfl NR				
Stiffness (Maximum)		S <sub>max</sub> NR				
Stiffness (Minimum)		S <sub>min</sub> NR				
Resistance to Permanent Deformation		F <sub>cmax</sub> NR				
Coarse Aggregate		BS EN 13043 - As Approved Supplier List				
Fine Aggregate		BS EN 13043 - As Approved Supplier List				
Filler Aggregate		BS EN 13043 (Natural or Extracted) - As Approved Supplier List				
Declaration of Performance		In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site <a href="https://www.newlayasphalt.co.uk/certification">https://www.newlayasphalt.co.uk/certification</a> (or will be supplied directly). The appropriate DoP is referenced NAAC002 UKCA DOP on the UKCA Regulations page and/or on formal documentation.			CPR DoP Electronic Provision No. 305/2011	